



## ATS Rackmount Switch



# DATA SHEET

☎ +44 20 8895 6455  
✉ [info@webbinfra.com](mailto:info@webbinfra.com)  
🌐 [www.webbinfra.com](http://www.webbinfra.com)

## ATS Rackmount switch

Webb rackmount ATS units have dual input power cords supplying power to the connected load. If the primary power source is interrupted or unavailable, the ATS will seamlessly source power from the secondary source without interrupting critical loads. It takes a maximum of 25 milliseconds to transfer the power from source 'A' to source 'B' to ensure uninterrupted power channels.

### Features

- In compliance with CE, ROHS standards
- Integrated LCDs for unit power indication
- Material: SPCC cold-rolled steel
- Integrated with standard dual inputs
- Consists of 250 volt AC, 50/60Hz Rating
- Available in 13, 16, 32 amperage ranges
- Available in single-phase or three-phase types
- Available in vertical or horizontal orientations
- Available with 2, 4, 6, 8, 10, 12 way socket outputs
- Available in BS1363, C13, C19 outlet types
- Available in BS1363, C14, IEC 60309 input types
- Available in 1m, 2m, 3m, or custom power cord lengths

*\*Specifications are subject to change without notice based on technical recommendations and related product enhancements*

## ATS RACK MOUNT SWITCH PART NUMBER KEY

Part Number: C.09.ATS.\_.\_. \_.\_.\_. \_.\_.\_.

C.09.ATS.Amperage.Phase.Orientation.Way.Type of outlets.Type of inputs.Cable length

Please add the codes from the tables below in the above format to derive your desired product part number

| Amperage | Code |
|----------|------|
| 13       | 13   |
| 16       | 16   |
| 32       | 32   |

| Phase  | Code |
|--------|------|
| Single | S    |
| Three  | T    |

| Orientation | Code |
|-------------|------|
| Vertical    | V    |
| Horizontal  | H    |

| Way | Code |
|-----|------|
| 2   | 02   |
| 4   | 04   |
| 6   | 06   |
| 8   | 08   |
| 10  | 10   |
| 12  | 12   |

| Type of outlet | Code |
|----------------|------|
| BS1363         | BS   |
| C13            | C3   |
| C19            | C9   |

| Type of input | Code |
|---------------|------|
| BS1363        | BS   |
| C14           | C4   |
| IEC 60309     | 69   |

| Cable length | Code    |
|--------------|---------|
| 2m           | 2       |
| 3m           | 3       |
| Custom       | Specify |

*\*Specifications are subject to change without notice based on technical recommendations and related product enhancements*