



CAT6A Keystone Jack



DATA SHEET

+44 20 8895 6455
info@webbinfra.com
www.webbinfra.com

CAT6A UTP Keystone Jack – 90°

WEBB CAT6A UTP keystone jacks are designed to meet or exceed TIA /EIA industry standards. They are available in universal label colors coded for T568A and T568B cabling schemes.

Features

- Compact jack design, 8 positions and 8 conductors
- Contact: phosphor bronze with 50µgold plate
- Universal label colors coded for T568A and T568B cabling schemes
- Designed for 22~26AWG solid cable
- High reliability and superior performance
- Force, RoHs, CE certified



**Specifications are subject to change without notice based on technical recommendations and related product enhancements*

Technical Specification

IDC Punch down cycle	250 Cycles (min.)
Insertion life	2000 Cycles (min.)
Operation temperature	40 ~ +70°C
Housing material	Fireproof ABS UL-94V0
Jack	8P8C 50 μinch gold plating
PCB	FR-4 / UL-94V0
IDC pin	Bronze & Tinned
Insulation resistance	500MΩ (min.)
Contact resistance	20MΩ (max.)
Current rating	1.5A
DC Resistance	0.1Ω (max.)
Withstanding voltage	1000 VAC RMS @ 60Hz/1min.

**Specifications are subject to change without notice based on technical recommendations and related product enhancements*