

Access Sensor



↓ +44 20 8895 6455 **∞** info@webbinfra.com **⊕** www.webbinfra.com



Environmental Monitoring

Webb environmental monitoring products permit you to actively monitor the conditions in BTS stations, warehouses, datacenters, colleges /educational institutes, hospitals, offices, restaurants, farmsteads, factories, museums or wherever it is essential to have a climate controlled environment. Upholding a constant & steady environment where equipment or products are housed is critical for operation, protection and usage in various industries. Conditions monitoring consist of temperature, humidity, power spikes and surges, liquid leakage, SNMP traps from other devices along with smoke & airflow.

Webb environmental monitoring equipment allows network machinists to detect conditions from a secure web interface and obtain SNMP, E-mails, and text message or siren/alert warnings when environmental sensors detect a breach in the preset thresholds. These products can also make you cognizant of the potential damages from critical failures. The Web interface can demonstrate live video surveillance and environmental magnitudes, which are logged to track patterns.

Secure Access T.10.530 / Access sensor

Utilize contact closure sensors, dry-contacts or PIR sensors to identify or sense when doors open or close. It triggers an alarm if any kind of activity occurs, and can also have commands sent to supporting devices such as alarms or sirens to take action.

Product Specifications

- This sensor is installed on doors
- Daisy chain unit with 150 meters maximum distance from the monitoring unit

*Specifications are subject to change without notice based on technical recommendations and related product enhancements

**** +44 20 8895 6455 **∞** info@webbinfra.com **⊕** www.webbinfra.com





Technical Specifications

| Dimensions | 60×18×18 mm |
|---------------------------|--|
| Weight | 106 g |
| Inputs | RJ-12 / RJ-11 |
| Operating characteristics | Temperature: minimum10° C - maximum.80° C, humidity: minimum. 5% - maximum. 95% (non-condensing) |
| Mounting | Mounting bracket included |
| Power consumption | 60 mW |
| Components | Manufactured in E.U |
| Maximum distance | 150 m |
| HS code | 8531 10 300 |
| Special features | Daisy chain |
| Package inclusion | Sensor, magnet, cable RJ11/RJ12 to RJ11/RJ12 (2m), screws M5 19mm 2pcs, washers M4 2pcs, nuts M4 2pcs, stickers 2pcs, mounting bracket |

*Specifications are subject to change without notice based on technical recommendations and related product enhancements

► +44 20 8895 6455
➡ info@webbinfra.com
₩ www.webbinfra.com