



DC Voltage Monitor



DATA SHEET

☎ +44 20 8895 6455
✉ info@webbinfra.com
🌐 www.webbinfra.com



Environmental Monitoring

Webb environmental monitoring products permit you to actively monitor the conditions in BTS stations, warehouses, datacenters, colleges /educational institutes, hospitals, offices, restaurants, farmsteads, factories, museums or wherever it is essential to have a climate controlled environment. Upholding a constant & steady environment where equipment or products are housed is critical for operation, protection and usage in various industries. Conditions monitoring consist of temperature, humidity, power spikes and surges, liquid leakage, SNMP traps from other devices along with smoke & airflow.

Webb environmental monitoring equipment allows network machinists to detect conditions from a secure web interface and obtain SNMP, E-mails, and text message or siren/alert warnings when environmental sensors detect a breach in the preset thresholds. These products can also make you cognizant of the potential damages from critical failures. The Web interface can demonstrate live video surveillance and environmental magnitudes, which are logged to track patterns.

Voltage / Current Meters

T.10.410/ DC voltage monitor

DC monitor is used for measurement of DC voltage up to 60V and converting data into format of IP monitoring system. The system interface allows you to assign the sensor and to introduce the function data conversion.

Product Specifications

- It's important to know that only 6P6C RJ12 cable is appropriate for this sensor.
- Maximum distance from the unit is 50 meters

**Specifications are subject to change without notice based on technical recommendations and related product enhancements*



Technical Specifications

| | |
|---------------------------|---|
| Dimensions | 60×18×18 mm |
| Weight | 100 g |
| Inputs | RJ-12 / RJ-11 |
| Operating characteristics | Temperature: minimum. -10° C - maximum.80° C, humidity: minimum. 5% - maximum. 95% (non-condensing) |
| Mounting | Desktop & wall mount |
| Power consumption | 100 mW |
| Components | Manufactured in E.U. |
| Max. distance | 50 m |
| HS code | 9030 33 300 |
| Package inclusion | Mounting bracket, sensor, nuts M4 2pcs, screws M5 19mm 2pcs, sticker, terminal plug 2 pins 5mm 1pc |
| Special features | Isolation - 1 kV, measured voltage - 0...60 V, accuracy - 1%. |

**Specifications are subject to change without notice based on technical recommendations and related product enhancements*