

Fibre Optic Splice Closure





DATA SHEET

info@webbinfra.com

⊕ www.webbinfra.com



Fibre Optic Splice Closure C.05.JC-D.102.144F.4

Joint closures are a range of products primarily used for joining cables. Joints in cables are a practical reality with the increase in distances that data needs to be transmitted. The primary function of a fiber optic joint closure is to protect the fiber joints from any physical damage.

Webb joint closures are made of high corrosion resistant polycarbonate material with heavy duty IP 68 delivering synthetic gaskets for total ingress protection. Our production treatments make our units UV resistant and waterproof. Every cable entry has high quality cable sealing plugs to maintain IP 68 ratings.



Applications

- Underground
- Pole mounting
- Aerial
- Wall mounting
- Vault

^{*}Specifications are subject to change without notice based on technical recommendations and related product enhancements



Features

- Can be utilized for notched, closed & rigid sheath platforms
- Suitable for the entire range of fibre optic cables
- Inclusive of sheath conservation and central strength member fasten feature
- Corrugated closure and light-weight plastic delivers robustness and resistance to chemical and UV degradation
- Requires only base level usage of tools during installation & re-entry
- Inclusive of the entire range of hardware & flash test option is available for closures
- Protection category: IP68
- RoHS compliance

Specifications

Part number	Splice tray	Spliced fibre-storage capacity (single fusion)		Height x diameter Size(mm)	Cable ports	Max. diameter of cable(mm)
C.05.JC-D.102A.144F.4	Tray 102A capacity : 24 splices	single fusion 144F(6 x 24F)	mass fusion(Ribbon) 432F(12F Ribbon) 288F(8F Ribbon) 432F(6F Ribbon) 288F(4F Ribbon)	540mm x 180 mm	1 oval port + 4 round ports	1 oval port for 1 cable with max 25 mm. 4 round ports ,each port
C.05.JC-D.102B.144F.4	Tray 102B capacity : 24 splices	144F(6 x 24F)	Not available		•	for 1 cable with max 20 mm

Optional Accessories

Туре	Code	
Earthing wire	C.05.OA.JC-EW	
Hoop for pole mount	C.05.OA.JC-H	
Transom for pole mount	C.05.OA.JC-T	
Bracket option for wall mount	C.05.OA.JC-B	
Sand paper	C.05.OA.JC-SP	
Anchor bolts	C.05.OA.JC-AB	

^{*}Specifications are subject to change without notice based on technical recommendations and related product enhancements