



## Fibre Optic Splice Closure



# DATA SHEET

☎ +44 20 8895 6455  
✉ [info@webbinfra.com](mailto:info@webbinfra.com)  
🌐 [www.webbinfra.com](http://www.webbinfra.com)



## Fibre Optic Splice Closure C.05.JC-D.316

Joint closures are a range of products primarily used for joining cables. Joints in cables are a practical reality with the increase in distances that data needs to be transmitted. The primary function of a fiber optic joint closure is to protect the fiber joints from any physical damage.

Webb joint closures are made of high corrosion resistant polycarbonate material with heavy duty IP 68 delivering synthetic gaskets for total ingress protection. Our production treatments make our units UV resistant and waterproof. Every cable entry has high quality cable sealing plugs to maintain IP 68 ratings.

### Features

- Protection for dome-end splice with mechanical seal, recyclable and suitable for re-entry
- Can be utilized for notched, closed & rigid sheath platforms
- Suitable for the entire range of fibre optic cables
- Inclusive of sheath conservation and central strength member fasten feature
- Corrugated closure and light-weight plastic delivers robustness and resistance to chemical and UV degradation.
- Requires only base level usage of tools during installation & re-entry
- Inclusive of the entire range of hardware & flash test option is available for closures
- RoHS compliance

### Applications

- Underground
- Aerial
- Vault
- Wall mounting
- Water tight

*\*Specifications are subject to change without notice based on technical recommendations and related product enhancements*



## Sealing Kits For Round Port



*\*Specifications are subject to change without notice based on technical recommendations and related product enhancements*

## Specifications

Part number	Splice tray	Spliced fibre storage capacity	Size(mm) height X diameter	Cable ports	Max. diameter of cable(mm)
C.05.JC-D.316A	Tray 204A capacity:24F	144 splices (6 x 24 splices)	450mm x 230 mm	1 large port + 4 round ports	1 large round port( for 1 loop cable with maxdia 16mm)+ 4 round ports(2 ports for 8 drop cable, 2 ports for cable with max dia 17.5mm or drop cable
C.05.JC-D.316B	Tray 204B capacity:24F	168 splices (7 x 24 splices)			

## Optional Accessories

Type	Code
Earthing wire	C.05.OA.JC-EW
Hoop for pole mount	C.05.OA.JC-H
Transom for pole mount	C.05.OA.JC-T
Bracket option for wall mount	C.05.OA.JC-B
Sand paper	C.05.OA.JC-SP
Anchor bolts	C.05.OA.JC-AB

*\*Specifications are subject to change without notice based on technical recommendations and related product enhancements*