

Fibre Optic Splice Closure





६ +44 20 8895 6455
∞ info@webbinfra.com

www.webbinfra.com



Fibre Optic Splice Closure C.05.JC-D.319

Joint closures are a range of products primarily used for joining cables. Joints in cables are a practical reality with the increase in distances that data needs to be transmitted. The primary function of a fiber optic joint closure is to protect the fiber joints from any physical damage.

Webb joint closures are made of high corrosion resistant polycarbonate material with heavy duty IP 68 delivering synthetic gaskets for total ingress protection. Our production treatments make our units UV resistant and waterproof. Every cable entry has high quality cable sealing plugs to maintain IP 68 ratings.

Features

- Can be utilized for notched, closed & rigid sheath platforms
- Suitable for the entire range of fibre optic cables
- Inclusive of sheath conservation and central strength member fasten feature
- Corrugated closure and light-weight plastic delivers robustness and resistance to chemical and UV degradation.
- Requires only base level usage of tools during installation & re-entry
- Inclusive of the entire range of hardware & flash test option is available for closures
- Protection category: IP68
- RoHS compliance

Applications

- Underground
- Aerial mounting

*Specifications are subject to change without notice based on technical recommendations and related product enhancements

**** +44 20 8895 6455 **** info@webbinfra.com **** www.webbinfra.com







*Specifications are subject to change without notice based on technical recommendations and related product enhancements

६ +44 20 8895 6455 **∞** info@webbinfra.com **⊕** www.webbinfra.com



Specifications

Part number	Adaptor	Spliced fibre storage capacity	Cable ports	Size(mm) height x diameter	Cable ports
C.05.JC-D.319	NO	48 splices (4 x 12 splices)	1 oval port + 1 round port	245 x 172 x 138mm	1 oval port for 1 looped cablewith max 20 mm. 1 round port for cable with max 30 mm or 8 drop cables with max 6 mm.
C.05.JC-D.319-8SC	8 SC SX adaptor	24 splices (2 x 12 splices)			

Optional Accessories

Туре	Code	
Earthing wire	C.05.OA.JC-EW	
Hoop for pole mount	С.05.ОА.ЈС-Н	
Transom for pole mount	C.05.0A.JC-T	
Bracket option for wall mount	C.05.0A.JC-B	
Sand paper	C.05.OA.JC-SP	
Anchor bolts	C.05.0A.JC-AB	

*Specifications are subject to change without notice based on technical recommendations and related product enhancements

↓ +44 20 8895 6455**☞** info@webbinfra.com**⊕** www.webbinfra.com