



## Fibre Pedestal



# DATA SHEET

☎ +44 20 8895 6455  
✉ [info@webbinfra.com](mailto:info@webbinfra.com)  
🌐 [www.webbinfra.com](http://www.webbinfra.com)

## Fibre Pedestal C.05.JC-D.BC6

These pedestals are developed explicitly for housing passive equipment and have direct-bury bases with an elevated rib appearance that do not necessitate stakes for installation. The direct-bury pedestal bases provide reliable & dependable installation and are not prone to slant. There is a stake mounting provision, which is optional feature to splice trench and similar applications. The lock system is very distinct with a self-locating safety option, which enables the pedestal to lock appropriately without any special arrangement.

These fibre pedestals hold joint closures as well as fibre breakout boxes for outdoor cable management

### Features

- 10" circular outline delivers finest workspace and turns radius supplies for the connectors & cables
- Convex pedestal design upholds a solid & firm appearance
- Assembled with robust & strong materials for exceptional security and elongated storage life
- Promotes installation standardization and saves space due to the usage of equipment mounting bracket
- Material of housing: HDPE
- Dimension:835mm(height) x 280mm(diameter)
- Single circuit splicing capacity(SC): 112 fibres-56 trays
- Single element splicing capacity(SE): 336 fibres-28 trays



*\*Specifications are subject to change without notice based on technical recommendations and related product enhancements*



## Ordering Information

Part number	Description
C.05.JC-D.BC6	Fibre Pedestal Type-3

## Optional Accessories

Type	Code
Earthing wire	C.05.OA.JC-EW
Hoop for pole mount	C.05.OA.JC-H
Transom for pole mount	C.05.OA.JC-T
Bracket option for wall mount	C.05.OA.JC-B
Sand paper	C.05.OA.JC-SP
Anchor bolts	C.05.OA.JC-AB

*\*Specifications are subject to change without notice based on technical recommendations and related product enhancements*