



# Fibre Optic Splice Closure



# DATA SHEET

☎ +44 20 8895 6455  
✉ [info@webbinfra.com](mailto:info@webbinfra.com)  
🌐 [www.webbinfra.com](http://www.webbinfra.com)

## Fibre Optic Inline Closure C.05.JC-L.101

Joint closures are a range of products primarily used for joining cables. Joints in cables are a practical reality with the increase in distances that data needs to be transmitted. The primary function of a fibre optic joint closure is to protect the fibre joints from any physical damage.

Webb joint closures are made of high corrosion resistant polycarbonate material with heavy duty IP 67 delivering synthetic gaskets for total ingress protection. Our production treatments make our units UV resistant and waterproof. Every cable entry has high quality cable sealing plugs to maintain IP 67 ratings.



*\*Specifications are subject to change without notice based on technical recommendations and related product enhancements*

## Features

- Corrugated closure and light-weight plastic delivers robustness and resistance to chemical and UV degradation
- Can be utilized for notched, closed & rigid sheath platforms
- Suitable for the entire range of fibre optic cables
- Inclusive of sheath conservation and central strength member fasten feature
- Requires only base level usage of tools during installation & re-entry
- Inclusive of the entire range of hardware
- Protection category: IP67
- RoHS compliance

## Applications

- Underground
- Vault
- Aerial
- Wall mounting

## Specifications

Part number	Spliced fibre storage capacity	Size(mm) L x W x H	Cable ports	Max.diameter of cable(mm)	Splice trays
C.05.JC-L.101.48	48 splices (4 x 12 splices)	280mm x 200mm x 90mm	2 ports	2 ports :each port for 1 cable with max 14 mm.or 2 cables with max 12 mm	Max.4 trays(each tray for 12 or 24 splices)
C.05.JC-L.101.96	96 splices (4 x 24 splices)				

*\*Specifications are subject to change without notice based on technical recommendations and related product enhancements*