



Fibre Optic Splice Closure



DATA SHEET

+44 20 8895 6455
info@webbinfra.com
www.webbinfra.com

Fibre Optic Inline Closure C.05.JC-L.106

Joint closures are a range of products primarily used for joining cables. Joints in cables are a practical reality with the increase in distances that data needs to be transmitted. The primary function of a fibre optic joint closure is to protect the fibre joints from any physical damage.

Webb joint closures are made of high corrosion resistant polycarbonate material with heavy duty IP 68 delivering synthetic gaskets for total ingress protection. Our production treatments make our units UV resistant and waterproof. Every cable entry has high quality cable sealing plugs to maintain IP 68 ratings.



Applications

- Duct
- Aerial
- Wall mounting

**Specifications are subject to change without notice based on technical recommendations and related product enhancements*

Features

- Recyclable and suitable for re-entry
- Can be utilized for notched, closed & rigid sheath platforms
- Suitable for the entire range of fibre optic cables
- Corrugated closure and light-weight plastic delivers robustness and resistance to chemical and UV degradation.
- Inclusive of sheath conservation and central strength member fasten feature
- Requires only base level usage of tools during installation & re-entry
- Inclusive of the entire range of hardware
- Protection category: IP68
- RoHS compliance

Specifications

Part number	Size(mm) L x W x H	Spliced fibre storage capacity	Cable ports	Max.diameter of cable(mm)	Splice trays
C.05.JC-L.106	432mm x 186mm x 100mm	Standard fibre, 96 splices (4 x 24 splices)	4 ports	4 ports: each port for 1 cable with max dia 22 mm	Max.4 trays(24 splices), each tray up to 24 splices

**Specifications are subject to change without notice based on technical recommendations and related product enhancements*