

Fibre Optic Splice Closure





& +44 20 8895 6455 **∞** info@webbinfra.com

www.webbinfra.com




Fibre Optic Inline Closure C.05.JC-L.136

Joint closures are a range of products primarily used for joining cables. Joints in cables are a practical reality with the increase in distances that data needs to be transmitted. The primary function of a fibre optic joint closure is to protect the fibre joints from any physical damage.

Webb joint closures are made of high corrosion resistant polycarbonate material with heavy duty IP 68 delivering synthetic gaskets for total ingress protection. Our production treatments make our units UV resistant and waterproof. Every cable entry has high quality cable sealing plugs to maintain IP 68 ratings.

Features

- Adequate for loading 1:8 and 1:16 PLC splitter
- Adequate for a maximum of 16SC adaptors
- Effortless access
- Requires only base level usage of tools during installation & re-entry
- Recyclable and suitable for re-entry
- Inclusive of the complete range of hardware



*Specifications are subject to change without notice based on technical recommendations and related product enhancements

**** +44 20 8895 6455 **\\$** info@webbinfra.com **\\$** www.webbinfra.com



Components

- Case, base, gasket seal, cable management & clamps
- Ground wire & splice try with heat deflated sleeves
- Insulation tape, buffer tube kit, cable tie & labels

Optional accessories

Duct & aerial mounting kits, relief valve & ground/earth system

Specifications

Part number	Size(mm) L x W x H	Spliced fibre storage capacity	Cable ports	Adaptor	Max.diameter of cable(mm)
C.05.JC-L.136	387mm × 203 mm × 88mm	Standard fibre 48 splices	8 ports for main cable, 16 ports for drop cable	Max. 16 SC adaptor	8 main cable ports: each for 1 cable with max 14mm. 16 drop cable ports: each for diameter 3mm or 3 x 2mm drop cables.

Applications

- Underground
- Wall mounting
- Aerial
- Duct mounting
- Pole mounting

*Specifications are subject to change without notice based on technical recommendations and related product enhancements

**** +44 20 8895 6455 **\\$** info@webbinfra.com **\\$** www.webbinfra.com