



Fibre Optic Splice Closure



DATA SHEET

☎ +44 20 8895 6455
✉ info@webbinfra.com
🌐 www.webbinfra.com

Fibre Optic Inline Closure C.05.JC-L.F02

Joint closures are a range of products primarily used for joining cables. Joints in cables are a practical reality with the increase in distances that data needs to be transmitted. The primary function of a fibre optic joint closure is to protect the fibre joints from any physical damage.

Webb joint closures are made of high corrosion resistant polycarbonate material with heavy duty IP 68 delivering synthetic gaskets for total ingress protection. Our production treatments make our units UV resistant and waterproof. Every cable entry has high quality cable sealing plugs to maintain IP 68 ratings.



**Specifications are subject to change without notice based on technical recommendations and related product enhancements*

Features

- Compacted design suitable for FTTH application
- Corrugated closure and light-weight plastic delivers robustness and resistance to chemical and UV degradation.
- Inclusive of sheath conservation and central strength member fasten feature
- Requires only base level usage of tools during installation & re-entry
- Inclusive of the entire range of hardware
- RoHS compliance

Applications

- Aerial
- Wall mounting
- Duct

Specifications

Part number	Dimension(mm)	Ports	Capacity	Material
C.05.JC-L.F02	179 x 72 x 26	2 ports, each port for max diameter 6mm	4 splices	MPP

**Specifications are subject to change without notice based on technical recommendations and related product enhancements*