



CAT6 S/FTP Patch Cord



DATA SHEET

☎ +44 20 8895 6455
✉ info@webbinfra.com
🌐 www.webbinfra.com



CAT6 S/FTP Patch Cord

WEBB CAT6 Screened foiled S/FTP patch cord are designed to meet and exceed ANSI/TIA/EIA 568B standards. WEBB patch cords are made by high-quality patch cable and RJ45 modular plug. These cables are simple, cost effective, reliable provides high speed transmission of data.

Features

- 250 MHz with over 2.5Gbps
- Shielded & Foiled
- RJ45 Connectors - Flash gold plated
- Durable for 750 insertion cycles
- Available in LSZH, PVC, PE sheaths
- Available in different lengths
- Available in different colors

Applications

- Data centre and telecommunication networks
- LAN applications
- CATV - cable television, CCTV

Technical Specifications

Conductor	Stranded bare copper
Insulations	Foamed polyethylene
Operating life	750 Insertion cycle
Dielectric pair	4 pairs
Conductor material	Copper
Contact material	Phosphor bronze
Contact plating	60μ gold
Overall diameter	5.7 ±0.30mm
Bending radius	15xOD
Contact resistance	30m Ω
Uninsulated resistance	150 MΩ/km minimum
Connector	RJ45
Cabling standard	EIA/TIA 568B
Flame retardance, smoke emission	IEC 60332-1, IEC 61034
Typical applications	IEEE 802.3: 10BASE-T; 100BASE-T; 1000BASE-T

**Specifications are subject to change without notice based on technical recommendations and related product enhancements*

PATCH CORDS PART NUMBER KEY

Part Number: C.04.C6.SF._ ._. .

C.04.Cable.Cable Construction.Length.Sheath.Color

Please add the codes from the tables below in the above format to derive your desired product part number

Cable	Code
CAT6	C6

Cable Construction	Code
SFTP	SF

Length	Code
1 meter	01
2 meter	02
3 meter	03
5 meter	05
Custom	C

Sheath	Code
PVC	P
LZOH	L

Color	Code
Grey	G
Black	B
Red	R
Blue	U
Yellow	Y
Orange	O

**Specifications are subject to change without notice based on technical recommendations and related product enhancements*