



CAT6A UTP Keystone Jack Tool Free -180°



DATA SHEET

☎ +44 20 8895 6455
✉ info@webbinfra.com
🌐 www.webbinfra.com



CAT6A UTP Keystone Jack Tool Free -180°

Webb Cat6A meets the EIA/TIA standard and provides a 180° termination design. Cat 6A keystone jack is a tool free model enabling termination without the help of a punch in tool.

Features

- 180 degrees punch down solid cable
- Meets or exceeds TIA /EIA standards.
- Phosphor bronze with 50µm gold plated
- Easy cabling fit for 110 punch-down tools
- Designed for 22~26AWG solid cable
- Force, RoHs, CE certified

Applications

- 100 BASE -T4(Fast Ethernet)
- POTS, T1 & Tq fractional
- 1 Gbps Ethernet (IEEE802.3)
- 100 Mbps TP-PMD
- POTS, T1 & Tq fractional
- 4/16 Mbps Token ring (IEEE802.5)
- 100 BASE- T (Fast Ethernet)
- 100VG-Any LAN (IEEE802.12)
- 52/155 Mbps ATM (ATM Forum)
- 10 BASE-T(IEEE802.3)
- 10 Gbps Ethernet

Technical Specifications

Insertion life	800 cycles
IDC life	250 times (22-26 AWG solid cable)
Insertion force	30N max. (IEC 60603-7-5)
Contact material	Phosphor bronze, gold plating (0.5mm)
IDC material	Phosphor bronze stamp pin (0.35mm)
Housing material	PC UL94V-0
Plating	Gold 50µm", silver (1.25µm, 5µm)
Insulation resistance	> 500 MΩ
Dielectric strength	1000 VDC (contact/contact), 1500 VDC (contact/ground)

**Specifications are subject to change without notice based on technical recommendations and related product enhancements*