



CAT6 Flat Travelling Cable



DATA SHEET

☎ +44 20 8895 6455
✉ info@webbinfra.com
🌐 www.webbinfra.com

CAT6 Flat Travelling Cable

Features

- Flexible for travelling
- Soft-annealed electrolytic copper conductor
- Insulation with properties according to EN 50214
- CE RoHS standard product

Technical Specification

No. of conductors	9
Conductor size	0.15mm +/- 0.02mm
Conductor	Bare copper
No. of pair	1 x 4pr
Insulation color	Pair 1 : Brown – white/brown Pair 2 : Green – white/green Pair 3 : Blue – white/blue Pair 4 : Orange – white/orange
Insulation diameter	1mm +/- 0.10mm
Sheath	Available in LSZH, PVC, PE sheaths
Core color	Pair 1 : Brown Pair 2 : Green Pair 3 : Blue Pair 4: Orange
Core sheath diameter	2.40mm +/- 0.20mm
Core identifications	Color
Outer sheath diameter	12.60mm x 4.25mm (Approx)
Outer sheath color	Available in all standard colors
Outer sheath dimension	As per EN 50214
Packing	1000 Meters drum
Free suspension length	Max.45 m
Running speed	Upto 4 m/s

**Specifications are subject to change without notice based on technical recommendations and related product enhancements*



LAN CABLES PART NUMBER KEY

Part Number: C.04.C6._._._._._

C.04.Cable.Indoor/Outdoor.Cable Construction.Sheath.Color

Please add the codes from the tables below in the above format to derive your desired product part number

Cable	Code
CAT6	C6

Cable Construction	Code
FLAT / LIFT	FLAT

Indoor/Outdoor	Code
Indoor	ND
Outdoor	OD

Sheath	Code
PVC	P
LZOH	L
Polyethylene	E

Color	Code
Grey	G
Black	B
Custom	Specify

**Specifications are subject to change without notice based on technical recommendations and related product enhancements*