



Copper Patch Panel



DATA SHEET

☎ +44 20 8895 6455
✉ info@webbinfra.com
🌐 www.webbinfra.com

1U CAT6 24 Ports UTP 3x8 Colored Jacks Patch Panel

19" standard size for mounting into server racks and network cabinets. This patch panel is designed for 22-26 AWG solid conductors and 1U Height (24 ports) with screws covered. The 3x8 colored jacks can be adjustable as per customer needs.

Features

- UTP 1U CAT6 colored jacks patch panel with 24 ports
- 19" mountable
- Designed for 22-26 AWG solid conductors
- 3x8 colored jacks with a customizable option



**Specifications are subject to change without notice based on technical recommendations and related product enhancements*



Specifications

- IDC - PC UL94V-0
- PCB - FR-4 1.60 mm (0.06") two impenetrable layers
- Housing: ABS 94V-0
- Contacts: 0.35 mm (0.014") phosphor bronze with 1.27-micron (50 micro inches) gold coating on contact area
- Metal housing: 1.50 mm dense metal
- Color pattern of conductors according to T568B & T568A
- Numerical display of ports on the front side of the panel with supplementary space for assigning numbers
- Color and numerical display of IDC modules at the panel rear

Electrical Characteristics

- Basis UL 1863
- Current rating: 1.5 A maximum
- Voltage ranking: 150 V
- Operation temperature: -40 ~+ 70 degrees centigrade
- Contact resistance: 20 mohm
- Insulation: 500 mohm
- Dielectric voltage resistance: 1000 V AC RMS, 60Hz/1minute

Product Description

Part number	C.08.CPP.C6.24.UTPS.M.L
Certificate	CE, ISO & ROHS
Number of ports	24
Shield	UTP
Windows label display	Yes

**Specifications are subject to change without notice based on technical recommendations and related product enhancements*