



## Copper Patch Panel



# DATA SHEET

☎ +44 20 8895 6455  
✉ [info@webbinfra.com](mailto:info@webbinfra.com)  
🌐 [www.webbinfra.com](http://www.webbinfra.com)

# 1U CAT6A 48 Ports FTP Network Patch Panel

It is commonly used in a local area network (LAN) as a mounted hardware assembly that contains ports to connect and manage incoming and outgoing ethernet cables. It is a network patch panel with 48 ports.

## Features

- FTP 1U CAT6A network patch panel with 48 ports
- 19" mountable
- Designed for 22-26 AWG solid conductors



*\*Specifications are subject to change without notice based on technical recommendations and related product enhancements*



## Specifications

- IDC - PC UL94V-0
- PCB - FR-4 1.60 mm (0.06") two impenetrable layers
- Housing: ABS 94V-0
- Contacts: 0.35 mm (0.014") phosphor bronze with 1.27-micron (50 micro inches) gold coating on contact area
- Metal housing: 1.50 mm dense metal
- Color pattern of conductors according to T568B & T568A
- Numerical display of ports on the front side of the panel with supplementary space for assigning numbers
- Color and numerical display of IDC modules at the panel rear

## Electrical Characteristics

- Basis UL 1863
- Current rating: 1.5 A maximum
- Voltage ranking: 150 V
- Operation temperature: -40 ~+ 70 degrees centigrade
- Contact resistance: 20 mohm
- Insulation: 500 mohm
- Dielectric voltage resistance: 1000 V AC RMS, 60Hz/1minute

## Product Description

Part number	C.08.CPP.CA.48.FTP.S.B.L
Certificate	CE, ISO & ROHS
Number of ports	48
Shield	FTP
Windows label display	Yes
Numerical display	Yes

*\*Specifications are subject to change without notice based on technical recommendations and related product enhancements*