

20 Pair Connection Box





DATA SHEET

44 44 20 8895 6455

info@webbinfra.com

info@webbinfra.com

⊕ www.webbinfra.com



20 Pair Connection Box

It is a wall mounted 20 pair voice connection box constructed in Mid Grey incombustible PVC, supplied with 2 off 10 pair LSA connection or disconnection modules and Its principal use is to build connection for CW1297/1308 voice cabling.

Features

- Attainable with two 10 pair LSA connection or disconnection modules
- Dust-tight box is applicable for indoor wire distribution
- Material: ABS plastic
- Mount frame: 1mm thickness stainless steel
- Cable access is through lid knockout features
- Two screws secure the lid to keep it firmly in place
- Internal cable management features incorporating integral jumper rings and a 10-way earth bar
- A detachable button in the center of the lid grants room for customized logos
- Mark up field to underside of lid for labelling and tag
- Optional deep lid version allows for fitment of protector mount 5B, providing over voltage protection using arrestors
- Flat lid logo dimension (h x w x d): 170 x 120 x 35mm, Deep lid logo dimension (h x w x d): 170 x 120 x 54

Ordering Information

No.	Description	Webb Part Number	Dimension (mm)
1	PVC Distribution Box 20 pair	C.04.DB.20.ND.E	170 x 120 x 35mm
2	PVC Distribution Box 50 pair	C.04.DB.50.ND.E	258 x 107 x 90mm
3	PVC Distribution Box 100 pair	C.04.DB.100.ND.E	320 x 209 x 122mm
4	Metal Distribution Box 340 pair	C.04.DB.340.ND.E	1100 x 280 x 150mm
5	Metal Distribution Box 680 pair	C.04.DB.680.ND.E	1100 x 500 x 150mm
6	Metal Distribution Box 1020 pair	C.04.DB.1020.ND.E	1100 x 720 x 150mm

^{*}Specifications are subject to change without notice based on technical recommendations and related product enhancements